

TESTED TO COMPLY WITH BOTH



ASTM
E3022-18
Standard

Rolls-Royce
RRES 90061
Requirements

MEETS
EN ISO:3059
Specifications

SPECTROLINE®
NDT

EDGE™ 13 SERIES

Compliant LED UV-A Flood Lamp

EDG-13SBLC

Standard-intensity **ASTM E3022-18** and **Rolls-Royce RRES 90061** compliant broad-beam flood lamp for overhead nondestructive testing inspections.

IP65
RATED



Dust Tight & Water Resistant



NDT Inspection Booths



Screening of Fluorescent Particles

EASILY MOUNTABLE

For overhead inspection or in-line applications

FLEXIBLE ARM

For mounting at specific angles

FANLESS

Cool running design that uses state-of-the-art heat sinks

THERMAL CUT-OFF CIRCUITRY

Prevents lamp from going out of compliance when internal temperature exceeds specifications

INTEGRAL UV-A PASS FILTERS

Reduce visible wavelengths

GANGABLE

Can be ganged together to provide an even wider coverage area

LONG-LASTING UV-A LENSES

Virtually eliminate clouding/solarization

13 UV-A LEDs

Provides large area of coverage for the largest, most even overhead beam available



CERTIFICATE OF CONFORMANCE & VALIDATION REPORT
included with each lamp

EDGE™ 13 SERIES EDG-365SBLC

MODEL	NOMINAL STEADY-STATE UV-A (365 nm) INTENSITY at 15 in (38 cm)	VISIBLE LIGHT MEASUREMENT	UV-A COVERAGE AREA (at minimum 1,200 µW/cm ²)
EDG-13SBLC	4,700 µW/cm ²	< 1 foot-candle (11 lux)	14.5 x 13 in (37 x 33 cm)

- Light Source:** (13) UV-A (365 nm) LEDs
- Lamp Style:** Panel flood lamp
- Length: (L x W x H)** 11 x 14 x 9 in (28 x 36 x 23 cm)
- Weight:** 14 lb (6.4 kg)
- Power Requirements:** AC power (main AC power cord supplied with the unit) (Available in 100-120V, 230V and 240V versions)

Ⓢ UV-A intensity reading taken with the Spectroline® AccuMAX™ Series meter, and are factory set to the values shown.



For applications requiring extremely large coverage areas, the EDGE™ 13 can be quickly ganged together.

*Optional accessory: ganged cables with connectors (130156)



SPECTROLINE® Validation Report				
MODEL NUMBER: EDG-13SBLC STANDARD: Robt-Royce RRES 9001			SERIAL NUMBER: PART NUMBER:	
TEST DESCRIPTIONS	PARAMETERS	TYPE TEST	NOMINAL	UNIT TEST
Minimum Working Distance	5,000 µW/cm ²	NA	15 inches	NA
	1,200 µW/cm ²	NA	10.5 inches	NA
Peak Wavelength	365 ±1.5 nm	367 ±1.2 nm	367 ±1.2 nm	368 ±1.2 nm
	50% Max PW ±10 nm (FWHM)	10 ±1.1 nm	10 ±1.1 nm	10 ±1.1 nm
Wavelength Drift	30% Max PW ±10 nm	-5 ±1.6 nm	-5 ±1.6 nm	-5 ±1.6 nm
	10% Max PW ±10 nm	22 ±1.3 nm	22 ±1.3 nm	22 ±1.3 nm
Visible Light Output	<10 µW/cm ² at 15 in	NA	5 minutes	NA
	<2% variation over 60 mins	NA	5 minutes	NA
Ambient Temperature	10 degrees C to 30 degrees C	25 degrees C	25 degrees C	50 degrees C
Source Life*	11,200 - 70% Initial Intensity	11,200 h	T502 =	NA
Life at 100% Intensity	11,200 - 100% Initial Intensity	11,200 hours	T502 =	NA



SPECTROLINE® Certificate of Conformance		
MODEL NUMBER: EDG-13SBLC STANDARD: ASTM E3022, Type A		SERIAL NUMBER: PART NUMBER:
APPARATUS 6.0	MANUFACTURER	MODEL NUMBERS
UV-A/Visible Meter (6.1)	Spectroline Corporation	AccuMax XRF-3000*
Spectroradiometer (6.2)	Std/NIST	UVI 50-25, NR 3-25
Spectrophotometer (6.3)	Std/NIST	UVI 50-25, NR 3-25
LAMP ACCEPTANCE TEST (8.1)	Requirements	At Ambient: 77° (25 C) (25±10°F)
Maximum Intensity (8.1)	At 15 inches (38 cm)	4700 µW/cm ²
Minimum Spectrum (7.6.4.1)	Min range 100-400nm	See Figure 7.6.4.1
Peak Wavelength (7.6.4.2)	360 to 370nm	NA
FWHM (7.6.4.3)	±15nm	NA
Longest Wavelength at Half Maximum (7.6.4.4)	±37nm	NA
UV-A LED Visible Light (Emission at 370 nm) (8.0)	<10 (21 Lum)	NA
Visible LED Light (Emission at 370 nm) (8.0)	<0.001 (0.100 Lux)	NA



UV-A Beam Profiles

