

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

Safety Data Sheet date: 10/11/2022, version 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: N120 SATWIPES PROSAT SOCOSAT
SDS code: P29212
UFI: PTY1-T3C2-K00Y-6CR7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Solvent
Industrial uses
Professional uses

Uses advised against:

No uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Manufacturers:

Socomore SASU
Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France
Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Distributors:

BabbCo-Socomore NDT Division
SherwinBabbCo
Tel: +33 (0)1.30.80.81.98
e-mail: sherwinbabbco@sherwinbabbco.eu
www.babbco.fr

Competent person responsible for the safety data sheet:

e-mail: babbco@babbco.fr

1.4. Emergency telephone number

France : ORFILA (INRS) +33 (0)1 45 42 59 59
International : CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)



Danger, Flam. Liq. 2, Highly flammable liquid and vapour.



Warning, Skin Irrit. 2, Causes skin irritation.



Warning, Eye Irrit. 2, Causes serious eye irritation.



Warning, STOT SE 3, May cause drowsiness or dizziness.



Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P273 Avoid release to the environment.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

None

Contains

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

acetone; propan-2-one; propanone

heptane; n-heptane

propan-2-ol; isopropyl alcohol; isopropanol

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.























3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 40\%$ - $< 50\%$	HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS	EC: 927-510-4 REACH No.: 01-21194755 15-33	2.6/2 Flam. Liq. 2 H225 3.2/2 Skin Irrit. 2 H315 3.10/1 Asp. Tox. 1 H304 3.8/3 STOT SE 3 H336 4.1/C2 Aquatic Chronic 2 H411
$\geq 30\%$ - $< 40\%$	acetone; propan-2-one; propanone	Index number: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 REACH No.: 01-21194713 30-49	2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336 EUH066

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

>= 15% - < 20%	heptane; n-heptane	Index number: CAS: EC:	601-008-00-2 142-82-5 205-563-8	 2.6/2 Flam. Liq. 2 H225  3.10/1 Asp. Tox. 1 H304  3.2/2 Skin Irrit. 2 H315  3.8/3 STOT SE 3 H336  4.1/A1 Aquatic Acute 1 H400  4.1/C1 Aquatic Chronic 1 H410
>= 10% - < 12.5%	propan-2-ol; isopropyl alcohol; isopropanol	Index number: CAS: EC: REACH No.:	603-117-00-0 67-63-0 200-661-7 01-21194575 58-25	 2.6/2 Flam. Liq. 2 H225  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336
>= 0.5% - < 1%	cyclohexane	Index number: CAS: EC:	601-017-00-1 110-82-7 203-806-2	 2.6/2 Flam. Liq. 2 H225  3.10/1 Asp. Tox. 1 H304  3.2/2 Skin Irrit. 2 H315  3.8/3 STOT SE 3 H336  4.1/A1 Aquatic Acute 1 H400  4.1/C1 Aquatic Chronic 1 H410
>= 0.5% - < 1%	n-hexane	Index number: CAS: EC:	601-037-00-0 110-54-3 203-777-6	 2.6/2 Flam. Liq. 2 H225  3.7/2 Repr. 2 H361f  3.10/1 Asp. Tox. 1 H304  3.9/2 STOT RE 2 H373  3.2/2 Skin Irrit. 2 H315  3.8/3 STOT SE 3 H336  4.1/C2 Aquatic Chronic 2 H411 Specific Concentration Limits: C >= 5%: STOT RE 2 H373

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a CO2 fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Store under the same conditions as a combustible solid product.

Store at ambient temperature. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

Always keep in a well ventilated place.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

- OEL Type: National - TWA: 1000 mg/m³ - STEL: 1500 mg/m³ - Notes: France

- OEL Type: National - TWA: 1600 mg/m³, 395 ppm - Notes: ExxonMobil

acetone; propan-2-one; propanone - CAS: 67-64-1

- OEL Type: National - TWA(8h): 1200 mg/m³ - Notes: Germany - Notes DFG

- OEL Type: National - TWA(8h): 1210 mg/m³, 500 ppm - STEL: 2420 mg/m³, 1000 ppm - Notes: France VLEC - TMP N° 84

- OEL Type: EU - TWA(8h): 1210 mg/m³, 500 ppm

- OEL Type: ACGIH - TWA(8h): 250 ppm - STEL: 500 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

- OEL Type: National - TWA: 1200 mg/m³, 500 ppm - STEL(15'): 4800 mg/m³, 2000 ppm - Notes: Österreich

- OEL Type: National - TWA(8h): 1210 mg/m³, 500 ppm - STEL(): 3620 mg/m³, 1500 ppm - Notes: United Kingdom

heptane; n-heptane - CAS: 142-82-5

- OEL Type: National - TWA(8h): 1668 mg/m³, 400 ppm - STEL: 2085 mg/m³, 500 ppm - Notes: France VLEC - TMP N° 84

- OEL Type: EU - TWA(8h): 2085 mg/m³, 500 ppm

- OEL Type: ACGIH - TWA(8h): 400 ppm - STEL: 500 ppm - Notes: CNS impair, URT irr

- OEL Type: National - TWA(8h): 2100 mg/m³, 500 ppm - Notes: Germany

- OEL Type: National - TWA(8h): 2085 mg/m³, 500 ppm - Notes: United Kingdom

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

- OEL Type: National - STEL: 980 mg/m³, 400 ppm - Notes: France

- OEL Type: National - TWA: 500 mg/m³, 200 ppm - Notes: DFG, Y - Germany

- OEL Type: National - TWA: 999 mg/m³, 400 ppm - STEL: 1250 mg/m³, 500 ppm - Notes: United Kingdom

- OEL Type: ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Notes: A4, BEI - Eye and URT irr, CNS impair

- OEL Type: National - TWA: 999 mg/m³, 400 ppm - STEL: 1250 mg/m³, 500 ppm

- OEL Type: OSHA PEL - TWA: 980 mg/m³, 400 ppm

- OEL Type: NIOSH REL - TWA: 980 mg/m³, 400 ppm - STEL: 1225 mg/m³, 500 ppm

- OEL Type: National - TWA: 500 mg/m³, 200 ppm - STEL(30min (Miw)): 1960 mg/m³, 800 ppm - Notes: Österreich

cyclohexane - CAS: 110-82-7

- OEL Type: National - TWA(8h): 700 mg/m³, 200 ppm - Notes: Germany

- OEL Type: National - TWA(8h): 700 mg/m³, 200 ppm - STEL: 1300 mg/m³, 375 ppm

- Notes: France VLEC - INRS TMP N° 84

- OEL Type: EU - TWA(8h): 700 mg/m³, 200 ppm

- OEL Type: ACGIH - TWA(8h): 100 ppm - Notes: CNS impair

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

- OEL Type: National - TWA(8h): 700 mg/m³, 200 ppm - STEL(15'): 2800 mg/m³, 800 ppm - Notes: Österreich
- OEL Type: National - TWA(8h): 200 ppm - Notes: Cyprus
- OEL Type: National - TWA(8h): 700 mg/m³ - STEL: 2000 mg/m³ - Notes: Czech Republic
- OEL Type: National - TWA: 50 ppm - Notes: Denmark
- OEL Type: National - TWA(8h): 350 mg/m³, 100 ppm - STEL(15'): 1050 mg/m³, 300 ppm - Notes: United Kingdom
- n-hexane - CAS: 110-54-3
 - OEL Type: National - TWA(8h): 72 mg/m³, 20 ppm - Notes: France VLEC - Note R3
 - INRS TMP N° 59, 84
 - OEL Type: National - TWA(8h): 180 mg/m³, 50 ppm - Notes: Germany
 - OEL Type: EU - TWA(8h): 72 mg/m³, 20 ppm
 - OEL Type: ACGIH - TWA(8h): 50 ppm - Notes: Skin, BEI - CNS impair, peripheral neuropathy, eye irr
 - OEL Type: National - TWA: 72 mg/m³, 20 ppm - STEL(15min (Miw)): 288 mg/m³, 80 ppm - Notes: Österreich
 - OEL Type: National - TWA(8h): 72 mg/m³, 20 ppm - Notes: UK

DNEL Exposure Limit Values

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

- Worker Industry: 300 mg/kg b.w./day - Worker Professional: 300 mg/kg b.w./day - Consumer: 149 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
- Worker Industry: 2085 mg/kg b.w./day - Worker Professional: 2085 mg/kg b.w./day - Consumer: 447 mg/kg b.w./day - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
- Consumer: 149 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects
- acetone; propan-2-one; propanone - CAS: 67-64-1
 - Worker Industry: 2420 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects - Notes: 1h
 - Worker Industry: 186 mg/kg - Consumer: 62 mg/kg - Exposure: Human Dermal - Frequency: Short Term (acute) - Notes: 8h for workers, 24h for consumer
 - Worker Industry: 1210 mg/m³ - Consumer: 200 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term (acute) - Notes: 24h for consumer
 - Consumer: 62 mg/kg - Exposure: Human Oral - Frequency: Short Term (acute)
 - Worker Industry: 500 ppm - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
- heptane; n-heptane - CAS: 142-82-5
 - Worker Industry: 300 mg/kg - Consumer: 149 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 - Worker Industry: 2085 mg/m³ - Consumer: 447 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 - Consumer: 149 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
 - Worker Industry: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 - Worker Industry: 500 mg/kg - Consumer: 89 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 - Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- n-hexane - CAS: 110-54-3
 - Worker Industry: 773 mg/kg b.w./day
 - Worker Industry: 2035 mg/m³

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

PNEC Exposure Limit Values

acetone; propan-2-one; propanone - CAS: 67-64-1
 Target: Fresh Water - Value: 10.6 mg/l
 Target: Marine water - Value: 1.06 mg/l
 Target: Freshwater sediments - Value: 30.4 mg/kg
 Target: Marine water sediments - Value: 3.04 mg/kg
 Target: Soil - Value: 29.5 mg/kg
 Target: Microorganisms in sewage treatments - Value: 100 mg/l
 Target: Water (intermittent discharge) - Value: 21 mg/l
 propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
 Target: Fresh Water - Value: 140.9 mg/l
 Target: Marine water - Value: 140.9 mg/l
 Target: Freshwater sediments - Value: 552 mg/kg
 Target: Marine water sediments - Value: 552 mg/kg
 Target: Soil (agricultural) - Value: 28 mg/kg
 Target: Microorganisms in sewage treatments - Value: 2251 mg/l
 Target: Water (intermittent discharge) - Value: 140.9 mg/l
 Target: Oral (secondary poisoning) (foodstuff) - Value: 160 mg/kg

Biological Exposure Index

n-hexane - CAS: 110-54-3
 Value: 5 mg/g - medium: Urinary creatinine - Biological Indicator: 2.5-hexanedione in the urine - Sampling Period: End of turn - Source: IBE

8.2. Exposure controls

Eye protection:
 Safety goggles (EN 166)
 Use closed fitting safety goggles, don't use eye lens.
 Protection for skin:
 Chemical protection clothing. (type 3 - EN14605)
 Protection for hands:
 Suitable gloves type: NF EN374
 NBR (nitrile rubber).
 PVA (Polyvinyl alcohol).
 Respiratory protection:
 Use adequate protective respiratory equipment.
 Mask with filter "A1" , brown colour (NF EN14387)
 Thermal Hazards:
 None
 Environmental exposure controls:
 None
 Appropriate engineering controls:
 None
 Other conditions affecting workers exposure:
 None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid coated on wipes	--	--
Colour:	Colourless	--	--
Odour:	N.A.	--	--
Melting point/freezing point:	Not Relevant	--	--
Boiling point or initial boiling point and boiling	>56°C	--	acetone

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

range:			
Flammability:	Flam. Liq. 2, H225	--	--
Lower and upper explosion limit:	0.6-13%	--	--
Flash point (°C):	< 21°C	--	--
Auto-ignition temperature:	215 °C	--	--
Decomposition temperature:	N.A.	--	--
pH:	N.A.	--	--
Kinematic viscosity:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	< 240 hPa (20°C)	--	--
Density and/or relative density:	N.A.	--	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

9.2. Other information

No other relevant information

Volatile Organic compounds - VOCs = 700 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 20 mg/l

acetone; propan-2-one; propanone - CAS: 67-64-1

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5800 mg/kg
 Test: LC50 - Route: Inhalation - Species: Rat = 76 mg/l - Duration: 4h
 Test: LD50 - Route: Skin - Species: Rabbit > 15800 mg/kg

heptane; n-heptane - CAS: 142-82-5

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
 Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
 Test: LC50 - Route: Inhalation > 20 mg/l

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 4570 mg/kg
 Test: LC50 - Route: Inhalation - Species: Rat = 20 mg/l - Duration: 8h
 Test: LC50 - Route: Inhalation Vapour - Species: Rat > 25000 mg/m3 - Duration: 6 hours
 Test: LD50 - Route: Skin - Species: Rabbit = 12.800 mg/kg

Reproductive toxicity:

Test: NOAEL - Route: Oral - Species: Rat = 500 mg/kg

STOT-repeated exposure:

Test: NOAEL - Route: Inhalation - Species: Rat = 1.3 mg/l
 Test: NOAEL - Route: Inhalation Vapour - Species: Rat (Male, female) = 12.5 mg/l

cyclohexane - CAS: 110-82-7

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg
 Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
 Test: LC50 - Route: Inhalation Vapour - Species: Rat > 19.1 mg/l - Duration: 4h

n-hexane - CAS: 110-54-3

Acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 23.3 mg/l - Duration: 4h
 Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
 Test: LD50 - Route: Skin - Species: Rabbit > 2800 mg/kg

If not differently specified, the information required in Regulation (EU)2020/878 listed below must be considered as N.A.:

Acute toxicity;
 Skin corrosion/irritation;
 Serious eye damage/irritation;
 Respiratory or skin sensitisation;
 Germ cell mutagenicity;
 Carcinogenicity;
 Reproductive toxicity;
 STOT-single exposure;
 STOT-repeated exposure;
 Aspiration hazard.

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

Other toxicological information:

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS
 May cause mild and transient eye discomfort.
 May be fatal if swallowed and enter the respiratory tract.

-

acetone; propan-2-one; propanone

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

Skin corrosion / irritation (rabbit):
Slight irritating effect
Severe eye injury/irritation (rabbit):
Irritating effect
-

heptane; n-heptane
Causes skin irritations, prolonged contact: dermatosis by removing the lipo-acid skin coating.
-

propan-2-ol; isopropyl alcohol; isopropanol
Severe eye damage/irritation:
Irritating to eyes
Foetal development:
Toxic effects on foetal development at doses that produce effects in mothers.
No teratogenic effects, NOAEL: 400 mg/kg Maternal no-effect concentration 400 mg/kg (rat)
Absence of toxic effects on foetal development. NOAEL: > 480 mg/kg. Maternal No-effect
Concentration: 240 mg/kg (rabbit)
Inhalation:
Irritating to eyes and respiratory tract (vapour, 1.0 mg/l)
-

cyclohexane
Inhalation:
Avoid inhalation of vapours: may cause lung inflammation.
Respiratory irritation:
Coughing, mucus production and shortness of breath

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.
HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Algae > 10 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata
Endpoint: LC50 - Species: Daphnia = 3 mg/l - Duration h: 48 - Notes: Daphnia magna
Endpoint: LC50 - Species: Fish > 13.4 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss
Endpoint: DSEO-R (NOELR) - Species: Algae = 6.3 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata

b) Aquatic chronic toxicity:

Endpoint: EL50
- Species: Daphnia = 1.6 mg/l - Duration h: 504 - Notes: Daphnia magna
Endpoint: DSEO-R (NOELR) - Species: Daphnia = 1 mg/l - Duration h: 504 - Notes: Daphnia magna
Endpoint: DSEO-R (NOELR) - Species: Fish = 1.53 mg/l - Duration h: 672 - Notes: Oncorhynchus mykiss

acetone; propan-2-one; propanone - CAS: 67-64-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: Salmo gairdneri
Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 96 - Notes: Pseudokirchneriella subcapitata
Endpoint: NOEC - Species: Algae = 430 mg/l - Duration h: 96 - Notes: Prorocentrum minimum, marine water

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 2212 mg/l - Duration h: 672 - Notes: Daphnia pulex

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

heptane; n-heptane - CAS: 142-82-5

a) Aquatic acute toxicity:

Endpoint: EL50

- Species: Fish > 1 mg/l - Notes: LL/EL/IL50

Endpoint: EL50

- Species: Daphnia > 1 mg/l - Notes: LL/EL/IL50

Endpoint: EL50

- Species: Algae > 1 mg/l - Notes: LL/EL/IL50

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1 mg/l

Endpoint: NOEC - Species: Daphnia > 0.1 mg/l

c) Bacteria toxicity:

Endpoint: EL50

- Species: bacteria > 10 mg/l

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 48 - Notes: Leuciscus melanotus

Endpoint: LC50 - Species: Fish = 9640 mg/l - Duration h: 96 - Notes: Pimephales promelas

Endpoint: LC50 - Species: Daphnia > 10.000 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72 - Notes: Scenedesmus subspicatus

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: NOAEC - Species: Algae = 1800 mg/l - Duration h: 84 - Notes: Algues vertes / Green algae

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 100 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata

c) Bacteria toxicity:

Species: bacteria = 1.050 mg/l

cyclohexane - CAS: 110-82-7

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Aquatic invertebrates > 10 mg/l - Notes: Daphnia magna

Endpoint: EC50 - Species: Aquatic invertebrates < 100 mg/l - Notes: Daphnia magna

Endpoint: EL50

- Species: Daphnia = 3 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: LC50 - Species: Fish = 4.5 mg/l - Duration h: 48 - Notes: Fathead Minnow

Endpoint: LL50

- Species: Fish > 13.4 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: EL50

- Species: Algae > 10 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata

Endpoint: EC50 - Species: Aquatic plants = 9.317 mg/kg/d - Duration h: 36 - Notes:

Selenastrum capricornutum

Endpoint: DSEO-R (NOELR) - Species: Algae = 10 mg/l - Duration h: 72 - Notes:

Pseudokirchneriella subcapitata

b) Aquatic chronic toxicity:

Endpoint: EL50

- Species: Aquatic invertebrates = 1.6 mg/l - Duration h: 504 - Notes: Daphnia magna

Endpoint: LOEC

- Species: Aquatic invertebrates = 0.32 mg/l - Duration h: 504 - Notes: Daphnia magna

Endpoint: NOEC - Species: Aquatic invertebrates = 0.17 mg/l - Duration h: 504 - Notes:

Daphnia magna

Endpoint: DSEO-R (NOELR) - Species: Daphnia = 1 mg/l - Duration h: 504 - Notes: Daphnia magna

n-hexane - CAS: 110-54-3

a) Aquatic acute toxicity:

Endpoint: EL50

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

- Species: Daphnia = 3 mg/l
Endpoint: EL50
- Species: Algae > 10 mg/l - Notes: Pseudokirchneriella subcapitata
Endpoint: LL50
- Species: Fish > 13.4 mg/l - Notes: Oncorhynchus mykiss
Endpoint: DSEO-R (NOELR) - Species: Algae = 10 mg/l - Duration h: 72 - Notes: Pseudokirchneriella subcapitata
- b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Daphnia = 0.17 mg/l - Duration h: 504
Endpoint: LOEC
- Species: Daphnia = 0.32 mg/l - Duration h: 504
- 12.2. Persistence and degradability**
HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS
Biodegradability: Readily biodegradable - Duration: 28 days - %: 98
acetone; propan-2-one; propanone - CAS: 67-64-1
Biodegradability: Readily biodegradable - Duration: 28 days - %: 91
Biodegradability: Chemical Oxygen Demand (COD) - Notes: 2,21 g O₂/g matière
heptane; n-heptane - CAS: 142-82-5
Biodegradability: Biodegradability rate - Duration: 28 days - %: 98
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
Biodegradability: Readily biodegradable - Duration: 5 days - %: 53 - Notes: Aerobie, activated sludge
Biodegradability: Oxidizes rapidly by photochemical reactions in air.
Biodegradability: Photodegradation (in air) - overall half-life time - Test: Degradation by OH radicals: Direct photolysis - Duration: 33 hours
cyclohexane - CAS: 110-82-7
Biodegradability: Biodegradability rate - Duration: 28 days - %: 9
Biodegradability: Manometer Breathing - Duration: 28 days - %: 77
n-hexane - CAS: 110-54-3
Biodegradability: Biodegradability rate - Duration: 28 days - %: 98
- 12.3. Bioaccumulative potential**
HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS
Oxidizes rapidly by photochemical reactions in air.
acetone; propan-2-one; propanone - CAS: 67-64-1
BCF 3
Log Pow - 0.24 - Notes: 20 °
Log Kow 0.17 - Notes: 20 °C
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
Estimated not significantly bioaccumulative.
Log Pow <=4
Log Kow 0.05 - Notes: 25°C
cyclohexane - CAS: 110-82-7
Log Kow 3.44
- 12.4. Mobility in soil**
HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS
Floats on the water. Adsorption in soil, low mobility.
acetone; propan-2-one; propanone - CAS: 67-64-1
Volality (H: Henry's Law Constant) 2929-3070 Pa.m³/mol - Notes: 25 °C (low volatility)
- 12.5. Results of PBT and vPvB assessment**
vPvB Substances: None - PBT Substances: None
- 12.6. Endocrine disrupting properties
No endocrine disruptor substances present in concentration >= 0.1%
- 12.7. Other adverse effects
No harmful effects expected.

SECTION 13: Disposal considerations

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

N.A.

SECTION 14: Transport information



14.1. UN number or ID number

ADR-UN Number: 3175
IATA-UN Number: 3175
IMDG-UN Number: 3175

14.2. UN proper shipping name

ADR-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS, ACETONE; PROPAN-2-ONE; PROPANONE)

IMDG-Shipping Name: SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C (HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS, ACETONE; PROPAN-2-ONE; PROPANONE)

14.3. Transport hazard class(es)

ADR-Class: 4.1
ADR - Hazard identification number: 40
IATA-Class: 4.1
IATA-Label: 4.1
IMDG-Class: 4.1

14.4. Packing group

ADR-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II

14.5. Environmental hazards

ADR-Environmental Pollutant: Yes
IMDG-Marine pollutant: Yes
IMDG-EmS: F-A , S-I

14.6. Special precautions for user

ADR-Subsidiary hazards: -
ADR-S.P.: 216 274 601
ADR-Transport category (Tunnel restriction code): 2 (E)
IATA-Passenger Aircraft: 445
IATA-Subsidiary hazards: -
IATA-Cargo Aircraft: 448
IATA-S.P.: A46
IATA-ERG: 3L
IMDG-Subsidiary hazards: -
IMDG-Stowage and handling: Category B
IMDG-Segregation: -
Q.L.: 1K
Q.E.: E2

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

14.7. Maritime transport in bulk according to IMO instruments
N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
Regulation (EU) n. 2021/849 (ATP 17 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3
Restriction 40

Restrictions related to the substances contained:

Restriction 57
Restriction 75

Listed or in compliance with the following international inventories:
N.A.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:
HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS (CAS: 64742-49-0)

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

N120 SATWIPES PROSAT SOCOSAT
aliphatic hydrocarbons >= 30%

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

Where applicable, refer to the following regulatory provisions :

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c, E2

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H319 Causes serious eye irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Repr. 2	3.7/2	Reproductive toxicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2

This safety data sheet has been completely updated in compliance to Regulation 2020/878.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

N120 SATWIPES PROSAT SOCOSAT - P29212

Aquatic Chronic 2, H411	Calculation method
-------------------------	--------------------

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold
CCNL - Appendix 1
Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.
SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product. The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
N120 SATWIPES PROSAT SOCOSAT - P29212

STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.