

Master item code: R 764S1 SPRAY

Safety Data Sheet date: 29/12/2023, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: R764S1SPRAY SDS code: R764S1SPRAY

UFI: TR1K-D3NJ-2009-UCJE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Developer

1.3. Details of the supplier of the safety data sheet

Manufacturers:

BABBCO

15, rue des Frères Lumière Z.I. des EBISOIRES 78370 PLAISIR (France)

Tel: +33 (0)1.30.80.81.82

www.babbco.fr **Distributors**:

BabbCo-Socomore NDT Division

BABBCO

SHERWIN-BABBCO Tel: +33 (0)1.30.80.81.82

www.babbco.fr

Competent person responsible for the safety data sheet:

e-mail: regulatoryservice@babbco.fr

1.4. Emergency telephone number

France: ORFILA (INRS) +33 (0)1 45 42 59 59 International: CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

Warning, Eye Irrit. 2, Causes serious eye irritation.

Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger



Hazard statements:

H222, H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Special Provisions:

None

Contains

propan-2-ol; isopropyl alcohol; isopropanol

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number		Classification
>= 30% - < 40%	propan-2-ol; isopropyl alcohol; isopropanol	CAS: EC:	603-117-00-0 67-63-0 200-661-7 01-21194575 58-25	2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336
>= 0.001% - < 0.1%	Quartz	CAS: EC:	14808-60-7 238-878-4	Substance with a Union workplace exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.



In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam.

Multipurpose powders class ABC

Water haze

Extinguishing media which must not be used for safety reasons:

Spray water

5.2. Special hazards arising from the substance or mixture

Carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use Self-Contained Breathing Apparatus (SCBA) with chemical protection suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Ensure adequate ventilation

For cleaning up:

Ensure adequate ventilation

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, ensure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Wash hands after use

Contamined clothing should be changed before entering eating areas.

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Store at ambient temperature. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Store at ambient temperatures. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.



Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

- OEL Type: National STEL: 980 mg/m3, 400 ppm Notes: France
- OEL Type: National TWA: 500 mg/m3, 200 ppm Notes: DFG, Y Germany
- OEL Type: National TWA: 999 mg/m3, 400 ppm STEL: 1250 mg/m3, 500 ppm Notes: United Kingdom
- OEL Type: ACGIH TWA(8h): 200 ppm STEL: 400 ppm Notes: A4, BEI Eye and URT irr, CNS impair
- OEL Type: National TWA: 999 mg/m3, 400 ppm STEL: 1250 mg/m3, 500 ppm
- OEL Type: OSHA PEL TWA: 980 mg/m3, 400 ppm
- OEL Type: NIOSH REL TWA: 980 mg/m3, 400 ppm STEL: 1225 mg/m3, 500 ppm
- OEL Type: National TWA: 500 mg/m3, 200 ppm STEL(30min (Miw)): 1960 mg/m3, 800 ppm Notes: Österreich

Quartz - CAS: 14808-60-7

- OEL Type: ACGIH TWA(8h): 0.025 mg/m3 Notes: (R), A2 Pulm fibrosis, lung cancer
- OEL Type: National TWA: 0.1 mg/m3 Behaviour: Binding Notes: France (fraction alvéolaire)
- OEL Type: National TWA: 0.1 mg/m3 Behaviour: Binding Notes: France (fraction de poussière alvéolaire)
- OEL Type: EU TWÁ: 0.1 mg/m3 Notes: Directive (EU) No. 2017/2398 (respirable fraction)
- OEL Type: National TWA: 0.05 mg/m3 Notes: Spain
- OEL Type: National TWA: 0.075 mg/m3 Notes: Netherlands
- OEL Type: National TWA: 0.05 mg/m3 Notes: Finland
- OEL Type: National TWA: 0.1 mg/m3 Notes: Denmark
- OEL Type: National TWA: 0.15 mg/m3 Notes: Austria
- OEL Type: National TWA: 0.15 mg/m3 Notes: Switzerland
- OEL Type: National TWA: 0.1 mg/m3 Notes: Poland
- OEL Type: National TWA: 0.1 mg/m3 STEL: 0.3 mg/m3 Notes: Norway
- OEL Type: National TWA: 0.1 mg/m3 Notes: Belgium
- OEL Type: National TWA: 0.07 mg/m3 Notes: Bulgaria
- OEL Type: National TWA: 0.1 mg/m3 Notes: Czech Republic
- OEL Type: National TWA: 0.1 mg/m3 Notes: Estonia
- OEL Type: National TWA: 0.15 mg/m3 Notes: Hungary [AK] (respirable)
- OEL Type: National TWA: 0.1 mg/m3 STEL: 0.2 mg/m3 Notes: Iceland
- OEL Type: National TWA: 0.1 mg/m3 Notes: Lithuania (IPRD)
- OEL Type: National TWA: 0.1 mg/m3 Notes: Romania
- OEL Type: National TWA: 0.1 mg/m3 Notes: Sweden

DNEL Exposure Limit Values

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

Worker Industry: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects



Worker Industry: 500 mg/kg - Consumer: 89 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic

effects

PNEC Exposure Limit Values

propan-2-ol: isopropyl alcohol: isopropanol - CAS: 67-63-0

Target: Fresh Water - Value: 140.9 mg/l Target: Marine water - Value: 140.9 mg/l

Target: Freshwater sediments - Value: 552 mg/kg Target: Marine water sediments - Value: 552 mg/kg

Target: Soil (agricultural) - Value: 28 mg/kg

Target: Microorganisms in sewage treatments - Value: 2251 mg/l

Target: Water (intermittent discharge) - Value: 140.9 mg/l

Target: Oral (secondary poisoning) (foodstuff) - Value: 160 mg/kg

Biological Exposure Index

N.A.

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Eye glasses with side protection.

Protection for skin:

Chemical protection clothing.

Protection for hands:

NR (natural rubber, natural latex).

Respiratory protection:

Mask with filter "A" , brown colour Mask with filter "P", white colour

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid		
Colour:	White		
Odour:	N.A.		
Melting point/freezing point:	N.A.		
Boiling point or initial boiling point and boiling range:	-44°C		
Flammability:	N.A.		
Lower and upper explosion limit:	Lower: 1.5 Vol% Upper: 12 Vol%		
Flash point (°C):	-97°C		
Auto-ignition temperature:	365°C		



Decomposition	N.A.	
temperature:		
pH:	N.A.	
Kinematic viscosity:	N.A.	
Solubility in water:	N.A.	
Solubility in oil:	N.A.	
Partition coefficient	N.A.	
n-octanol/water (log value):		
Vapour pressure:	8.300 hPa	
Density and/or relative	N.A.	
density:		
Relative vapour density:	N.A.	

Particle characteristics:

Particle size:	N.A.	
i ai liolo dizo.		

9.2. Other information

No other relevant information

Volatile Organic compounds - VOCs = 90.43 %

N.A. = not available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

R764S1SPRAY

Acute toxicity

Not classified

Based on available data, the classification criteria are not met

Skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

Serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

Respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

Germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

Carcinogenicity

Not classified



Based on available data, the classification criteria are not met

Reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

STOT-single exposure

The product is classified: STOT SE 3 H336

STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

Aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Adverse health effects

Skin and Eye contact:

It can cause irritation if comes in contcat with skin and/or eyes.

Toxicological information of the main substances found in the product:

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5840 mg/kg bw - Source: OECD 401 Test: LC50 - Route: Inhalation - Species: Rat > 10000 ppm - Duration: 6 hours -

Source: OECD 403

Test: LD50 - Route: Skin - Species: Rabbit = 13900 mg/kg bw - Source: OECD 402

Quartz - CAS: 14808-60-7

Acute toxicity:

Test: LC50 - Route: Oral = 500 mg/kg

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

Other toxicological information:

propan-2-ol; isopropyl alcohol; isopropanol

Severe eye damage/irritation:

Irritating to eyes

Foetal development:

Toxic effects on foetal development at doses that produce effects in mothers.

No teratogenic effects, NOAEL: 400 mg/kg Maternal no-effect concentration 400 mg/kg (rat)

Absence of toxic effects on foetal development. NOAEL: > 480 mg/kg. Maternal No-effect

Concentration: 240 mg/kg (rabbit)

Inhalation:

Irritating to eyes and respiratory tract (vapour, 1.0 mg/l)

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. R764S1SPRAY

Not classified for environmental hazards

Based on available data, the classification criteria are not met propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 1800 mg/l - Duration h: 168 - Notes: green algae

Endpoint: EC50 - Species: Water flea = 10000 mg/l - Duration h: 48

Endpoint: EC50 - Species: Fathead minnow (Pimephales promelas) = 9640 mg/l - Duration h:

96

Endpoint: LL/EL/IL50 - Species: Fish > 100 mg/l



Endpoint: LL/EL/IL50 - Species: Algae > 100 mg/l

Endpoint: LL/EL/IL50 - Species: Microorganisms > 100 mg/l

d) Terrestrial toxicity:

Endpoint: IC50 - Species: Lactuca sativa < 2104 mg/kg - Duration h: 72

12.2. Persistence and degradability

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

Biodegradability: Readily biodegradable - Duration: 5 days - %: 53

Biodegradability: DThO - %: 72

12.3. Bioaccumulative potential

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

Estimated not significantly bioaccumulative.

Log Pow 0.05

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

07 07 04* other organic solvents, washing liquids and mother liquors Additional disposal information:

Disposal should be in accordance with applicable regional, national and local laws and regulations. Please consult Technical Data Sheet for details.

SECTION 14: Transport information



14.1. UN number or ID number

ADR-UN Number: 1950 IATA-UN Number: 1950 IMDG-UN Number: 1950

14.2. UN proper shipping name

ADR-Shipping Name: AEROSOLS, flammable AEROSOLS, flammable AEROSOLS, flammable

14.3. Transport hazard class(es)

ADR-Class: 2
ADR - Hazard identification number: -

IATA-Class: 2.1 IMDG-Class: 2.1

IMDG-Class: 2

14.4. Packing group

ADR-Packing Group: IATA-Packing group: IMDG-Packing group: -



14.5. Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: Nο F-D . S-U IMDG-EmS:

14.6. Special precautions for user

ADR-Subsidiary hazards: See SP63 ADR-S.P.: 190 327 344 625

ADR-Transport category (Tunnel restriction code): 2 (D)

IATA-Passenger Aircraft: 203 IATA-Subsidiary hazards: See SP63 203

IATA-Cargo Aircraft:

IATA-S.P.: A145 A167 A802 IATA-ERG: 10L

IMDG-Subsidiary hazards: See SP63 IMDG-Stowage and handling: **SW1 SW22** IMDG-Segregation: **SG69**

Q.L.: 1L Q.E.: E0

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 75

Listed or in compliance with the following international inventories:



Labelling of detergents (EC Regulations 648/2004 and 907/2006): N.A.

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

N.A.

Where applicable, refer to the following regulatory provisions:

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive) Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P3a

15.2. Chemical safety assessment

Nο

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Hazard class and hazard category	Code	Description
Aerosols 1	2.3/1	Aerosol, Category 1
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222, H229	On basis of test data
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:



ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van

Nostrand Reinold CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality: this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden. SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product. The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LTE: Long-term exposure.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STE: Short-term exposure.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

STOT SE: May cause drowsiness or dizziness



TLV: Threshold Limiting Value.
TWA: Time-weighted average

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day.

(ACGIH Standard).

WGK: German Water Hazard Class.