

B105 **SOLVENT**

Approvals and conformities

- ASME
- ASTM-E-1444
- EDF (PMUC : Produits et Matériels Utilisables en Centrale)
- ISO 9934-2
- NFF 00-090
- RCC-M

MANUFACTURER : BABBCO (FR)

DESCRIPTION / APPLICATION(S) :

Primarily to wipe off the white background B104B used for magnetic testing.

Can also be used as a degreasing agent prior to penetrant testing, although cleaner N120 is better.

Companion products : White background B104B

DIRECTIONS FOR USE

To wipe off the B 104B white background after magnetic testing, spray B 105 and wipe with a rag, until the white layer disappears.

TECHNICAL CHARACTERISTICS

- Non-chlorinated propelling agent
- Highly volatile, low toxicity product, offering a pleasant fruity smell

Halogenous content < 200ppm
Sulfur content < 200ppm

PRECAUTIONS FOR USE AND STORAGE

Transport / Handling : Refer to Material Safety Data Sheet (MSDS).

Storage : Keep away from moisture

Temperature range : 0°C à 50° C (32°F to 122°F).

Keep packaging closed after taking out some of the product

This technical data sheet replaces and cancels the previous one.

The information in this document is given in good faith but is only indicative and therefore does not imply any commitment or guarantee on our part, particularly in the event of infringement of rights belonging to third parties as a result of using our products. These data should not be used as a substitute for the preliminary tests that must be carried out to ensure the suitability of the product in each specific case. In any case, we invite you to check the local legislation applicable to the use of our product. Pictures are non-contractual.