

Technical Data Sheet

Approvals and conformities

ASME

EDF (PMUC : Produits et Matériels Utilisables en Centrale)

RCC-M

ISO 3452-2

MANUFACTURER: BABBCO (Fr) / SOCOMORE (Fr)

DESCRIPTION / APPLICATION(S)

A particularly powerful general-purpose mixture, designed to remove the most varied impurities and spots on surfaces before penetrant testing.

Companion product(s): Can be used before any penetrant application, in the "normal range of temperature (+10°C. to +50°C.)" as defined in ISO 3452-2. For other temperatures, please ask us.

DIRECTIONS FOR USE

To degrease a part, pour large quantities of N120 and wipe simultaneously with a clean cloth. The N120 evaporates quickly and leaves the part perfectly clean and clear of traces of lubricant, grease, oil, etc.

One may also use pre-impregnated wipes, particularly in a closed environment, as these limit emissions of vapor.

Ensure that cleaning is sufficient to remove pollutants from discontinuities as well as surface pollutants. Wait for the N120 to evaporate completely from the discontinuities before applying the penetrant.

TECHNICAL CHARACTERISTICS

- Very low halogen and sulfur content.
- Compatible with all metals, ceramics, and some synthetic substances.

Appearance colorless liquid







Flash point <	< -	18	3°	(2
---------------	-----	----	----	---	---

PRECAUTIONS FOR USE AND STORAGE

Transport / Handling:

See Safety Data Sheet (SDS)

Storage:

Keep away from moisture

Temperature limit: 0 to 50° C. (32 to 125°F.)

Keep the packaging closed after withdrawing the product.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.



